

# **EUROPLEX-228**

# **Complete Treatment for Low Pressure Boilers**

**Product Code: Q00057** 

**Product Group: BOILER WATER TREATMENT** 

Packaging: 25L

#### PRODUCT DESCRIPTION

EUROPLEX-228 is a liquid compound containing alkaline mineral salts, sequestering agents, dispersants, sludge conditioners, oxygen scavengers and volatile amines which provide scale, corrosion, oxygen and condensate control for low pressure boilers. EUROPLEX-228 provides a complete treatment for low preassure boilers.

#### **PRODUCT USES**

EUROPLEX-228 is suitable for all auxiliary boilers, waste heat units, low-pressure water tube boilers, smoke and water tube boilers, steam/steam generators etc.

### APPLICATION, DOSAGE & CONTROL

For an untreated system an initial dose of 2,5 liters of EUROPLEX-228 per 1000 liters of untreated water is recommended. Thereafter the dosage rate of EUROPLEX-228 is based on "P" alkalinity measured in ppm of CaCO<sub>3</sub>.

The following chart indicates the appropriate amount of EUROPLEX-228 to be added (the midpoint value is circled).

"P"Alkalinity ppm CaCO₃	0	50	100	150	200	225	250	300	350	400
EUROPLEX-228 L/1000 L	2,5	1,9	1,3	0,7	0	0	0	0	0	BLD

EUROPLEX-228 is best fed continuously to the boiler feed water by means of a metering pump.

The recommended control limits are:

p-Alkalinity: 100-300 ppm CaCO<sub>3</sub>.
Chlorides: 200 ppm Cl max.
Condensate: pH 8.3-9.0.

Phosphate: 10-80ppm.DEHA: 0.1-0.4 ppm.

Blowdown (BLD) and scumming operations must proceed at regular intervals to remove sludge/sediment particles. Excessive chlorides are removed by blowdown.

## **BENEFITS**

- Suitable for all boilers, up to 32 bar preassure.
- Cleans the boiler, reducing maintenance costs.
- Prevents corrosion.
- Provides scale inhibition.
- Neutralizes the acids in the condensate system.
- Confronts the low-pH corrosion of the condensate.
- More efficient heat transfer; energy saving.
- Easily removed sludge by blowdown, thanks to suspension.
- Easy to feed and control.
- Treatment level determined with a simple test kit.



### **HEALTH SAFETY**

Please refer to the Material Safety Data Sheet and Product Label for specific information.

## LIMITATION OF LIABILITY

EUROCHEM INTERNATIONAL standard <u>terms and conditions</u> of sale, available on request, apply and contain limitations on any liability that may be incurred by EUROCHEM INTERNATIONAL arising in any way from the sale and use of products supplied by EUROCHEM INTERNATIONAL.