



### EuroHot-Box

Euro Hot-Box connects at the outlet of a high pressure cleaner - maximum 500 bar pressure. It is built in metallic chassis with anticorrosion treatment and stainless steel cover. For use with feed water with maximum flow up to 18lpm.

#### FEATURES

- Vertical boiler with cooling forced air according to EU regulations for the atmospheric pollution
- Burner with mechanical system to pulverize the diesel oil according to EU regulations concerning energetic consumption
- Pressure of pulverization at 11 bar. Continuous service, with instantaneous stop of the diesel oil via electromagnetic valve
- Independent electric motor for the burner
- Main electric motor with elastic coupling driving the turbine and diesel pump
- Pump suitable to work with diesel oil or kerosene
- Restoration after the lack of diesel oil is automatic, no need for manual cleaning
- Flame control via photocell
- Asbestos free product
- Plastic fuel tank 30 ltr
- IP65 electric panel, with on/off switch, 0-150 degrees Celsius thermostat, electronic board for the operation of the photocell and power on indicator
- Auxiliary electric circuit at 24V
- Double passage of the fumes fixed on a refractory bottom
- Index opacity of the combustion gases not exceeding 1.5 degrees of Bacharach scale
- Boiler coil from special steel
- Plastic fuel tank 30 ltr

**Other voltages available upon request**