

KEM-SOOT-L

Product Code : Q00062

Product Group: FUEL OIL TREATMENT

Packaging: 25L, 210L

PRODUCT DESCRIPTION

KEM-SOOT-L low temperature soot remover is a unique, catalytic powder designed to effectively reduce exhaust deposits and to maintain clean heat transfer surfaces in exhaust gas boilers. Deposits in the exhaust system waste energy, cause corrosion, increase stack fire potential and can lead to costly repairs.

The low activation temperature 200° C of KEM-SOOT-L soot remover compliments and assures that the most efficient energy recovery systems remain free of exhaust deposits. KEM-SOOT-L soot remover works by reducing the ignition temperature of the organic deposits from incomplete combustion, which bind the adherent incombustible deposits. In doing so, exhaust deposits become friable losing their adherent properties, and are easily removed and eliminated during normal soot-blowing operations.

APPLICATION, DOSAGE & CONTROL

It is recommended that fuel deliveries are representatively sampled and analyzed to monitor overall fuel quality and to determine levels of contamination. Consult your local Eurochem International representative for further discussion on fuel samplers, fuel analysis services and onboard fuel testing.

Although designed specifically for use in diesel exhaust gas economizers, KEM-SOOT-L low temperature soot remover can be used in any fireside application such as:

- Firetube boilers
- Water-tube boilers/H.P. and L.P.
- Main boilers
- Donkey boilers
- Auxiliary boilers

The recommended dosage rate is 1 kg/day for every 400-500 m² of surface area to be treated. However, variations in fuel quality, engine load, boiler design, heating surface configuration and the amount of carbonaceous and incombustible deposits may alter this dosage rate. For vessels with exhaust gas temperatures below 250° C, it is recommended that the dosage rate be increased 1.5 kg/day for every 400-500 m² of surface area.

KEM-SOOT-L soot remover is usually slug dosed to the exhaust trunk using the KEM-SOOT-L dosing unit.

A. Exhaust Gas Economizer System

1. For this system, KEM-SOOT-L soot remover is injected just prior to the exhaust gas economizer inlet beyond the bypass damper (if one is fitted). However, dosing can take place anywhere in the system depending on where fouling is a problem.

2. In instances where the air stream is too fast to develop sufficient contact time, it may be necessary to partially bypass the economizer or slow the engine to half speed or less during dosing in order to achieve maximum product performance.

BENEFITS

- Maintains cleaner heat recovery transfer surfaces than soot blowing alone.
- Minimizes the risk of stack fires.
- Protects economizer asset from low-temperature corrosion.
- Easy to apply.
- Compliments modern high energy efficient diesel exhaust gas recovery systems.
- Effective in auxiliary boilers.
- Safely stored in dry, well ventilated area.



B. Oil Fired Boiler System

Due to variations in design and equipment, contact your local Eurochem International representative for specific instructions.

HEALTH SAFETY

Please refer to the Material Safety Data Sheet and Product Label for specific information.

LIMITATION OF LIABILITY

EUROCHEM INTERNATIONAL standard terms and conditions of sale, available on request, apply and contain limitations on any liability that may be incurred by EUROCHEM INTERNATIONAL arising in any way from the sale and use of products supplied by EUROCHEM INTERNATIONAL.