



OIL REMOVER-S

Product Code : Q00021

Product Group: SOLVENT BASED DEGREASERS & TANK CLEANERS

Packaging: 25L

PRODUCT DESCRIPTION

OIL REMOVER-S is a solvent emulsion cleaner with surfactants for fast effective cleaning.

PRODUCT USES

OIL REMOVER-S is ideal for removing mineral oils and greases from machinery parts, diesel engine exteriors, compressors exteriors, tank tops, bulkheads, decks, bunker tanks etc. Also is suitable for engine rooms decks and spot cleaning/degreasing of oil tanks.

APPLICATION & DOSAGE

OIL REMOVER-S may be used neat or diluted with petroleum or water in varying concentrations depending on the heaviness of the soil by soaking, spraying or combined with scrubbing.

Soaking: Parts are immersed in OIL REMOVER-S. Allow deposit to be broken up and loosened before removal. Then rinse off with water.

Spraying: Apply OIL REMOVER-S over all soiled areas. Allow time for OIL REMOVER-S to act, between 15-30 minutes, then rinse off by water hose.

Scrubbing: Use OIL REMOVER-S neat and agitate by scrubbing where soiling is stubborn. Rinse off with water.

Butterworth or steam cleaning machines: Use concentration of 0,1 – 1% at the nozzle.

APPROVAL

OIL-REMOVER-S is approved by The Greek Chemical State Laboratory with approval No. 13632/0/2009.

BENEFITS

- Safe to all metals, glass, plastic, wood and painted surfaces.
- Loosens and breaks up deposits.
- Leaves oil and grease free surfaces.
- Strong emulsifying action.
- Easy to use.
- Can be used as an all purpose degreaser.
- Saves time and effort.



HEALTH SAFETY

Please refer to the Material Safety Data Sheet and Product Label for specific information.

LIMITATION OF LIABILITY

EUROCHEM INTERNATIONAL standard terms and conditions of sale, available on request, apply and contain limitations on any liability that may be incurred by EUROCHEM INTERNATIONAL arising in any way from the sale and use of products supplied by EUROCHEM INTERNATIONAL.