



P.W.T

Product Code : Q00033

Product Group: POTABLE WATER TREATMENT

Packaging: 25L

PRODUCT DESCRIPTION

PWT is a concentrated product, based on phosphates and is specially designed to reduce the corrosion that is created in the storage systems of pot water. The product creates a protective film within the tank on the metal surfaces, which does not affect the colour, taste or smell of water. Besides phosphates, which is the base of PWT mixture, is officially recognized from EPA for usage in potable water systems.

PWT is used in potable water systems and other shipboard once-through water systems.

APPLICATION & DOSAGE

The product can be injected into the discharge lines of the fresh water generator or directly into the fresh water pumps' suction manifold. **POTABLE WATER TANKS** The initial recommended dosage is 1 liter of PWT per 20 tonnes of water. **TEMPORARY BALLAST TANKS OF POTABLE WATER** The initial recommended dosage is 1.5 liter of PWT per 20 liters of water. This provides a level of 12 ppm of phosphate salts. For a tank where PWT already exists, the recommended dosage is 1 liter of PWT per 20 tones of water.

BENEFITS

- Prevents 'red' water from iron and 'black' water from manganese in potable water systems
- Prevents corrosion (from low pH and/or dissimilar metals)
- Gradually removes existing scale deposits (from minerals)
- Cost effective
- Safe and easy to use

**HEALTH SAFETY**

Please refer to the Material Safety Data Sheet and Product Label for specific information.

LIMITATION OF LIABILITY

EUROCHEM INTERNATIONAL standard terms and conditions of sale, available on request, apply and contain limitations on any liability that may be incurred by EUROCHEM INTERNATIONAL arising in any way from the sale and use of products supplied by EUROCHEM INTERNATIONAL.